



TECHNICAL DATA	COMPACT SPECIAL
Composition	100% Solution Dyed Acrylic
Width	153 cm
Weight	310 gr/m ²
Length of rolls	50 ml
Finish	Water repellent Anti-stain treatment
Colour fastness to light	7/8 <small>UNE EN ISO 105-B02:2014</small>
Colour fastness to artificial weathering	4/5 <small>UNE EN ISO 105-B04:1998</small>
Tear resistance	Warp 49 N Weft 32 N <small>UNE EN ISO 13937-3:2001</small>
Breaking strength	Warp 1800 N Weft 860 N <small>UNE EN ISO 13934-1:2013</small>
Ultraviolet protection factor UPF	50+ <small>AZ/NZS 4399/1996</small>
Spray test	5/5 <small>UNE EN ISO 24920</small>
Water column mm	650 <small>UNE EN ISO 20811</small>
CLEANING INSTRUCTIONS	


Sensitive values of tolerance +/- 5 %



WATER
RESISTANT




STAIN
RESISTANT




MOULD
RESISTANT



UV
PROTECT



UV
RESISTANT




DURABLE
STRONG



NO
CONDUCTOR



EASY
TO CLEAN



DISINFECTABLE



BLEACH
friendly



The Agora warranty covers the fabric becoming unserviceable as a result of loss of colour or strength from normal exposure conditions, including sunlight, mildew, rot and atmospheric chemicals, when properly installed, used and maintained. The warranty does not cover labour and installation costs supplied by the dealer. The warranty neither applies against deterioration of any kind due to abusive use, accidental burns, negligence or perforations.

Waterproof and flame retardant treatments: Recommended for cushions and upholstery only. Always use the lamination face inside. Do not expose expose the coated side to sun or light.