








FIBER ART FOR PERFORMANCE FABRICS  
100% SOLUTION DYED ACRYLIC



TECHNICAL DATA	LISO WATERPROOF
Composition	100 % Solution Dyed Acrylic Lamination: 100 % PU
Width	155 cm
Weight	304 g/m <sup>2</sup>
Length of rolls	50 ml
Finish	Water repellent Anti-stain treatment
Colour fastness to light	7/8 <small>UNE EN ISO 105-B02:2014</small>
Colour fastness to artificial weathering	4/5 <small>UNE EN ISO 105-B04:1998</small>
Colour fastness to rubbing	4-5 /5 <small>UNE EN ISO 105-X12:2016</small>
Colour fastness to chlorinated water	5/5 <small>UNE EN ISO 105-E03:2010</small>
Tear resistance	Warp 170 N Weft 150 N <small>UNE EN ISO 13937-3:2001</small>
Breaking strength	Warp 1600 N Weft 800 N <small>UNE EN ISO 13934-1:2013</small>
Resistance to pilling	4-5 /5 <small>UNE EN ISO 12945-2:2001</small>
Ultraviolet protection factor UPF	50+ <small>AZ/NZS 4399/1996</small>
Spray test	5/5 <small>UNE EN ISO 24920</small>
Water column mm	1000 <small>UNE EN ISO 20811</small>
Abrasion resistance (Martindale)	20000 <small>UNE EN ISO 12947-1/2:2007-04</small>
CLEANING INSTRUCTIONS	
    	


Sensitive values of tolerance +/- 5 %



WATER  
RESISTANT




STAIN  
RESISTANT




MOULD  
RESISTANT



UV  
PROTECT



UV  
RESISTANT




DURABLE  
STRONG




NO  
CONDUCTOR



EASY  
TO CLEAN



DISINFECTABLE



BLEACH  
friendly



The Agora warranty covers the fabric becoming unserviceable as a result of loss of colour or strength from normal exposure conditions, including sunlight, mildew, rot and atmospheric chemicals, when properly installed, used and maintained. The warranty does not cover labour and installation costs supplied by the dealer. The warranty neither applies against deterioration of any kind due to abusive use, accidental burns, negligence or perforations.

Waterproof and flame retardant treatments: Recommended for cushions and upholstery only. Always use the lamination face inside. Do not expose the coated side to sun or light.