



## Produktspecifikation

Sjukhusväv PU/Pol Stretch art. no. 2056-0014

TEKNISKA EGENSKAPER			
Material	100 % Polyester		105 g/m <sup>2</sup>
Beläggning	100 % Polyuretan		95 g/m <sup>2</sup>
Totalvikt			200 g/m <sup>2</sup>
TESTRESULTAT			
Tensile Strength	Norm		EN ISO 1421
	Warp		>445 N
	Weft		>337 N
Elongation	Norm		EN ISO 1421
	Warp		>117 %
	Weft		>157 %
Hydrostatic Head	Norm		EN 20811
			>20 000 Pa
Hydrolysis according Jungle Test	after 3 weeks: no loss of quantity		
BEHANDLINGAR			
Flamskydd	BS 7175   Crib 5		
Antisvampskydd	Resistant Sanitized		ATCC #6538
Antibakteriellt	ASTM G 21-96		ATCC #4352 ATCC #6538 ATCC 33591 (MRSA)
Vattenångpermeabilitet	According standard: ASTM E-96 Method E		600g/(day.m <sup>2</sup> )-24h at 38C
Krympning vid tvätt i 95°C	Max 5	ISO 5077	< 2.00 %
Resistens mot desinfektionsmedel	Denaturated Alcohol	OK	90 % Alcohol + 90 Ether
	Fugaten Spray	OK	Ethanol 70 % (608 g/l)
			Olien 7 (g/l) 5 min. contact
	Other		H.A.C., Reocid, Dettoll, Lyorthol Indur Des., Prespect, Hycolin
Tvättinstruktioner			
Halogenfri			RoHS Directive 2011/65/EU
Antimonfri			EN 71-3 2013+A1 2014
Biocompabilitet			BS EN ISO 10993-5 & 10993-10